

4.2.2013 HYVINKÄÄ

Declaration of Conformity

Manufacturers declaration

This is a Manufacturers declaration on air permeability values (according to EN 29053) of Saint-Gobain Rakennustuotteet Oy ISOVER insulation products, additional to CE-marking.

Product	Air permeability
Light weight slabs	[x10 ⁻⁶ m ³ /msPa]
KL-40	< 180
KL-37	< 120
KL-35	< 90
KL-33	< 60
KL-32	< 50
KL-31	< 30
Light weight rolls	[x10 ⁻⁶ m ³ /msPa]
KT-42	< 220
KT-40	< 180
KT-40/Twin	< 180
KH	< 100
KT-37	< 120
KT-35	< 90
Wind barrier boards	[x10 ⁻⁶ m ³ /msPa]
SKL	< 50 (thickness 30 mm < 30)
RKL-31	< 30 (thicknesses 20...45 mm < 20)
VKL	< 15
Heavy weight boards	[x10 ⁻⁶ m ³ /msPa]
OL-E	< 50
FS5	< 50
FS5+	< 30
OL-A	< 25
FS30	< 30
OL-K	< 15

[x10⁻⁶ m³/msPa]

OL-P	< 20
OL-A-20; OL-A-30	< 15
OL-TOP	< 15

Products with airtight facings

Faced wind barrier boards

RKL-31 FACADE	facing tight (basic board 30 x10 ⁻⁶ m ³ /msPa)
RKL-31 FAÇADE EJ	facing tight (basic board 15 x10 ⁻⁶ m ³ /msPa)
RKL-31 A	facing tight (basic board 30 x10 ⁻⁶ m ³ /msPa)
RKL-31 EJ	facing tight (basic board 15 x10 ⁻⁶ m ³ /msPa)

Aluminium faced boards

REK	facing tight (basic board 30 or 10 x10 ⁻⁶ m ³ /msPa)
Sauna	facing tight (basic board 15 x10 ⁻⁶ m ³ /msPa)

The air permeability of these products is controlled by factory measurements of manufacturer.

Respectively,



Jussi Jokinen
Development manager
Saint-Gobain Rakennustuotteet Oy